



Main Feature

1. Small size (29x12.6x24.2 in mm) produces a switching capacity up to 16A for high density P.C.Board mounting technique.
2. The contact form construction is 1A
3. The Surge Resistance of BPMF series is 10,000V
4. Sealing Construction (Free from dust and solder flux):
BPMF-SS: Plastic Sealed Type.
5. The selection of plastic insulation material is designed for high temperature and provides better chemical solution performance.
6. RoHS Compliant.

Application

Air Conditioning, Fridge, Washing Machine, etc Household Appliances

Contact Rating

- Nominal Load(Resistive Load Cos $\phi = 1$)
Contact Capacity
BPMF-LM.....16A at 250VAC/30VDC
- Max. Allowable Current
BPMF-LM.....16A
- Max. Allowable Voltage
BPMF-LM.....AC250V/DC30V
- Max. Allowable Power Force
BPMF-LM.....3,840VA/480W
- Contact Material..... Ag Alloy
- Contact Form.....SPDT

Performance (at Initial Value)

- Contact Resistance..... $\leq 50m\Omega$ at 6VDC/1A
- Operate Time.....10ms. Max
- Release Time..... 5ms. Max
- Dielectric Strength:
Between Coil & Contact.....5,000VAC at 50/60 Hz
for one minute
Between Contacts.....1,000VAC at 50/60 Hz
for one minute
- Surge Resistance.....10,000V (between Coil
& Contact 1.2x50 μs)
- Insulation Resistance.....1,000 Mega Ω Min. at
500VDC

- Max. On/Off Switching:
Electrical.....30 Ops per minute
Mechanical.....300 Ops per minute
- Temperature Range..... - 40~85°C
- Humidity Range.....5%~85% RH
- Coil Temperature Rise..... 35°C Maximum
- Vibration:
Endurance.....10 to 55 Hz dual
amplitude width 1.5mm
Error Operation.....10 to 55 Hz dual
amplitude width 1.5mm
- Shock:
Endurance..... 981m/s² Min
Error Operation..... 98.1m/s² Min
- Life Expectancy:
Electrical.....10⁵ Operations at
Rated Resistive
load
Mechanical.....10⁷ Operations at
No load condition
- Weight.....about 15g

Safety Standard & Its File Number

- UL.....E332719
- CQC.....CQC11002062613
- TUV.....R50170592

Coil Specification (at 20 °C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 8\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
BPMF-LM	3	176.5	17	Abt. 0.54	75% Maximum	10% Minimum	130%
	5	108.7	46				
	6	89.6	67				
	9	60	150				
	12	44.4	270				
	24	21.8	1100				
	48	11.2	4270				

Ordering Information

BPMK-F	- S -	1	12	L	M	
						Contact Form: M:One form A
						Coil Type: L:Standard DC Coil
						Coil Voltage: 03:3V, 05:5V,06:6V,09:9V 12:12V,24:24V,48:48V
						Number of Pole: 1:One Pole
						Type of Sealing: SS:Plastic Sealed Type
						Type: BPMK-F

Classification

Model	BPMK-F
Coil Sensitivity	Standard DC Coil 1A
Flow Solder Type	BPMK-F -S-1□□LM

Dimension

