

Material
Housing: PA66, UL94V-0
Clamp: Phosphor bronze, Ni Plated
Screws: M2 Steel, Zinc plated
Cage: Brass, Zn plated
Slide block: Steel, Zn plated


Electrical
Rated voltage: 300V
Rated current: 8A
Contact Resistance: 20 mΩ
Insulation resistance: 500MΩ/DC500V
Withstand voltage: AC2000V / 1 min
Wire Range: 28 ~ 16AWG 1.0mm²

Mechanical
Temp. Range: -40 °C ~ +105 °C
Strip length: 7mm
Torque: 0.2Nm (1.8 bin)

Order Information

L-KLS2-EDKC-3.81-XXP-4S00

RoHS
Terminal Block
Pitch
No.: of Pole
Color: 4- Green
Screw: S-Slot Screw C-Cross Screw
Product Code: 00~99

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:	
X. ±0.60	.X ±0.38	.XX ±0.25	X. ±5°	.X ±3°	.XX ±2°
Draw by 2015-09-01			PROJECTION		 NingBo KLS ELECTRONIC CO.,L TD.
Check by 2015-09-15			UNITS mm		
SCALE			SHEET SIZE A4		
				Pluggable Terminal Block 3.81MM	
				KLS P/N: KLS2-EDKC-3.81-XXP-4S-00	