

*Material*  
Housing: PA66, UL 94 V-0  
Shrapnel: Stainless steel  
Clamp: Phosphor bronze, Tin plated



*Electrical*  
Rated voltage: 300 V  
Rated current: 8 A  
Contact Resistance: 20 mΩ  
Withstand voltage: AC 2000V / 1 Min  
Insulation resistance: 500 MΩ / DC 500V  
Wire Range: 24 ~ 16 AWG 1.0 mm<sup>2</sup>

*Mechanical*  
Temp. Range: -40 °C ~ +105 °C  
Strip length: 9-10mm

*Order Information*

L-KLS2-FMD-3.50-XXP-4 00

RoHS  
Terminal Block  
Pitch  
No.: of Pole  
Color: 4- Green  
Product Code: 00 ~ 99

GENERAL TOLERANCE	ANGLE TOLERANCE	Description:	
X. ±0.60	X. ±5°	Pluggable Terminal Block 3.5 MM	
.X ±0.38	.X ±3°	KLS P/N:	KLS2-FMD-3.50-XXP-4-00
.XX ±0.25	.XX ±2°	 NingBo KLS ELECTRONIC CO.,L TD.	
Draw by 2015-09-01	PROJECTION 		
Check by 2015-09-15	UNITS mm		
SCALE	SHEET SIZE A4		