

1	2		3	4	5		6	7		8	
A	RoHS Compliance			P/N	Nominal DC Spark-over voltage	Deviation of VS	Impulse spark-over voltage	Impulse discharge current	Insulation resistance	Capacitance	A
B					100V/s		1KV/μs	8/20μs 10cycles		1MHz	B
C				L-KLS5-GDT1206-090	90	±30%	≤600	0.5	≥10 ⁸	≤0.6	C
D				L-KLS5-GDT1206-120	120	±30%	≤650	0.5	≥10 ⁹	≤0.6	D
E				L-KLS5-GDT1206-150	150	±30%	≤700	0.5	≥10 ⁹	≤0.6	E
F				L-KLS5-GDT1206-200	200	±30%	≤750	0.5	≥10 ⁹	≤0.6	F
G				L-KLS5-GDT1206-230	230	±30%	≤750	0.5	≥10 ⁹	≤0.6	G
H				L-KLS5-GDT1206-300	300	±25%	≤850	0.5	≥10 ⁹	≤0.6	H
				L-KLS5-GDT1206-350	350	±25%	≤900	0.5	≥10 ⁹	≤0.6	
				L-KLS5-GDT1206-400	400	±25%	≤1000	0.5	≥10 ⁹	≤0.6	

PROJECTION		Description:	
		3.2x1.6x1.6mm SMD GAS DISCHARGE TUBE	
UNITS	mm	KLS P/N:	L-KLS5-GDT1206-XXX
SHEET SIZE	A4		
Draw:	Daniel	2020-06-29	NingBo KLS ELECTRONIC CO.,LTD.
Check:	Daniel	2020-06-29	