



Material
Housing: PA66,UL94V-0
Clamp: Copper alloy,Sn plated

Electrical
Rated voltage: 300V
Rated current: 16A
Withstand voltage: AC1600V / 1min
Wire Range: 22~12AWG 2.5mm²

Mechanical
Temp. Range: -40 °C ~ +105 °C
Soldering temperature: 260°C/5S
Strip length: 6~7mm
Screw/Torque: M2.5/0.4
Pin Dimensions: 0.8x1.0mm
PCB Hole Diameter: φ1.5

Order Information
L-KLS2-125-5.00-XXP-4 S 00

- RoHS
- Terminal Block
- Pitch:5.00mm
- No.: of Pole(02~24)
- Color: 4- Green
- Screw: S-Slot Screw
- Product Code: 00~99

GENERAL TOLERANCE	ANGLE TOLERANCE	Description:
X. ±0.60	X. ±5°	5.00mm Screw Terminal Block Rising clamp
.X ±0.38	.X ±3°	
.XX ±0.25	.XX ±2°	KLS P/N: L-KLS2-125-5.00-XXP-4S
Draw by 2022-03-01	PROJECTION	NingBo KLS ELECTRONIC CO.,L TD.
Check by 2022-03-15	UNITS mm	
SCALE	SHEET SIZE A4	

PCB LAYOUT