



7	8
Part Number	Current Rating
L-KLS5-274-G-040-A	40A
L-KLS5-274-G-050-A	50A
L-KLS5-274-G-080-A	80A
L-KLS5-274-G-100-A	100A
L-KLS5-274-G-150-A	150A
L-KLS5-274-G-200-A	200A
L-KLS5-274-G-250-A	250A
L-KLS5-274-G-300-A	300A
L-KLS5-274-G-400-A	400A
L-KLS5-274-G-500-A	500A

Characteristics:  
 Voltage Rating: 32V DC  
 Current Rating: 40A ~ 500A  
 Operating Temperature: -40°C to +125°C

Material:  
 Body: Bakelite  
 Contact: Copper Alloy, Gold Plated

Time-Current Characteristics

% of Rating	Opening Time
150	360s Min.
160	60s
220	60s Max.
250	0.8 to 10s
400	0.25 to 2s

ITEM	Description	Material	Q'ty	GENERAL TOLERANCE	PROJECTION	ANGLE TOLERANCE
5	Connector	Brass Alloy	2	X. $\pm 0.5$	UNITS	$\pm 5^\circ$
4	Transparent cover	PC, Transparent	1	.X $\pm 0.25$	SCALE	$\pm 3^\circ$
3	Cover	Bakelite, Black	1	.XX $\pm 0.15$	Draw by:	$\pm 2^\circ$
2	Base	Bakelite, Black	1		Check by:	
1	Contact	Copper Alloy, Gold Plated	1		Date	
					2022-09-01	
					SHEET	
					1 OF 1	

Description: 32V Marine Limiter Fuse

KLS P/N: L-KLS5-274-G-XXX-A

**KLS** NingBo KLS ELECTRONIC CO., L TD.