



| 7 | 8 |
|---------------------|----------------|
| Part Number | Current Rating |
| L-KLS5-274C-G-040-A | 40A |
| L-KLS5-274C-G-050-A | 50A |
| L-KLS5-274C-G-080-A | 80A |
| L-KLS5-274C-G-100-A | 100A |
| L-KLS5-274C-G-150-A | 150A |
| L-KLS5-274C-G-200-A | 200A |
| L-KLS5-274C-G-250-A | 250A |
| L-KLS5-274C-G-300-A | 300A |
| L-KLS5-274C-G-400-A | 400A |
| L-KLS5-274C-G-500-A | 500A |

Characteristics:
 Voltage Rating: 32V DC
 Current Rating: 40A ~ 500A
 Operating Temperature: -40°C to +125°C

Material:
 Body: Ceramic, White
 Contact: Copper Alloy, Gold Plated

Time-Current Characteristics

| % of Rating | Opening Time |
|-------------|--------------|
| 150 | 360s Min. |
| 160 | 60s |
| 220 | 60s Max. |
| 250 | 0.8 to 10s |
| 400 | 0.25 to 2s |

| ITEM | Description | Material | Q'ty | GENERAL TOLERANCE | PROJECTION | ANGLE TOLERANCE |
|------|-------------------|---------------------------|------|-------------------|------------|-----------------|
| 5 | Connector | Brass Alloy | 2 | X. ±0.5 | UNITS | mm |
| 4 | Transparent cover | PC, Transparent | 1 | .X ±0.25 | SCALE | 1:1 |
| 3 | Cover | Ceramic, White | 1 | .XX ±0.15 | Draw by: | Daniel |
| 2 | Base | Ceramic, White | 1 | ANGLE TOLERANCE | Check by: | Daniel |
| 1 | Contact | Copper Alloy, Gold Plated | 1 | X. ±5° | Date | 2022-09-01 |
| | | | | .X ±3° | SHEET | 1 OF 1 |
| | | | | .XX ±2° | | |

Description: 32V Marine Limiter Fuse

KLS P/N: L-KLS5-274C-G-XXX-A

KLS NingBo KLS ELECTRONIC CO., L TD.